RI8567 - 100kHz to12GHz RF Test Set

Cassini Instrument Profile

Applications

- Transceivers
- RFICs

 Multi-band Modules Microwave Components

Overview


The RI8567 Test Set combines a 2-port vector analyzer and complex receiver into a single test instrument. The versatile multi-port test set interfaces with a Cassini source for direct power, harmonic, distortion, and s-parameter measurements from 100 kHz to 12 GHz. With microsecond frequency switching and signal path calibration, the RI8567 can be shared across multiple RF ports for fast, precision measurements and maximum channel utilization.



Key Features

- S-Parameters from 100 MHz to 12 GHz
- Direct Power/Spectrum Measure
- 0.1 dB Measurement Resolution
- Microsecond Frequency Locking

Block Diagram





RI8567 - 100kHz to 12 GHz RF Test Set

Cassini Instrument Profile

Performance

Vector Analyzer

Frequency Range 100 MHz to 12 GHz

Power Range -100 dBm to +30 dBm

Exposer Resolution ±0.1 dB


Receiver

Frequency Range 100 kHz to 12 GHz

Power Range -115 dBm to +20 dBm

Meas. Bandwidth 7 kHz / 200 kHz / 5 MHz (selectable)

Inputs/Outputs



Cassini Test Systems

A versatile, high-speed, automated test solution for analog, mixed-signal, RF, and millimeter-wave devices.

Cassini provides a modular base architecture that is fully configurable via Test Instrument Modules (TIMs) to meet the needs of any IC, wafer, or module test requirement.

Each TIM contains internally-cooled, RF-shielded measurement instrumentation, signal distribution, and blind mate interfacing to provide targeted test resources and integrate to build up a complete production test platform.

Combined with Roos Instruments' integrated test software, Cassini can be configured to any application for maximum performance, true low cost of test, and the industry's fastest test times.

Roos Instruments 2285 Martin Ave. Santa Clara, CA 95050 TEL +1 - 408 - 748 - 8589 sales@roos.com www.roos.com CASSINI

ALL PRODUCT, PRODUCT SPECIFICATIONS, AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE PERFORMANCE, FUNCTION, DESIGN, OR OTHERWISE. The information in this publication is, to the best of our knowledge, accurate at the date of publication.